



Technical Data

AEROSOL-CANS

Aluminium, monobloc in accordance with **EN 15 008**

Material

- Aluminium 99,5

Manufacturing process

- Impact extruded without seam, shoulders being formed afterwards

Dimensions and finish

- Round, flat, and special shoulder
- Test pressure 12, 15 and 18 bar
- Opening corresponds to EN 15 006
- Shapes customized
- Embossing

Internal coating

- Internal lacquer applied in two layers and adapted to filling product
- Powder coating, solvent free
- Partial lacquering

Decoration

- Brushed finish
- Outside lacquer: clear, white or coloured
- Special-effect-lacquer: flitter and pearlescent
- Dry-Offset printing up to 8 colours
- Additional decoration can be achieved by half tone and irisated print
- Clear outside varnish, brilliant, mat and special-effect-lacquers





Technical Data

AEROSOL CANS

TUBEX-Standard sizes 1"
Opening EN 15 006

Brimfull capacity (ml)	Fill volume (ml)		Dimension (mm)	
	Liquid gas	Compressed gas	diameter	height
59	35	-	35	70
75	50	-	35	88
89	-	50	35	105
110	75	-	35	127
140	100	75	45	105
175	125	100	45	128
210	150	125	45	150
			50	125
			53	110
270	200	150	45	190
			50	156
			53	142
335	250	200	50	190
			53	173
405	300	250	53	205